

11-20-'06 16:22 FROM-TUNG & ASSOCIATES

12485404035

T-817 P04/15 U-252

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

IN THE CLAIMS

Please amend claim 1 as follows.

RECEIVED  
CENTRAL FAX CENTER  
NOV 20 2006

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

RECEIVED  
CENTRAL FAX CENTER

NOV 20 2006

Listing of Claims

1. (currently amended) An apparatus comprising:

a process chamber having a substantially vertical chamber wall defining a chamber interior;

a showerhead provided in said process chamber and having a lateral surface engaging said chamber wall; and

a plurality of exterior fasteners extending laterally through said chamber wall and into said showerhead, with said plurality of exterior fasteners structurally isolated from said chamber interior.

2. (original) The apparatus of claim 1 wherein each of said plurality of exterior fasteners comprises a fastener head and a threaded shank extending from said fastener head, and wherein said fastener head engages an exterior surface of said chamber wall.

3. (original) The apparatus of claim 1 further comprising a gas mix plate carried by said chamber wall above said showerhead.

4. (original) The apparatus of claim 3 wherein each of said plurality of exterior fasteners comprises a fastener head and a

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

threaded shank extending from said fastener head, and wherein  
said fastener head engages an exterior surface of said chamber  
wall.

5. (previously presented) The apparatus of claim 1 further  
comprising a confinement ring provided in said process chamber  
beneath said showerhead.

6. (original) The apparatus of claim 5 wherein each of said  
plurality of exterior fasteners comprises a fastener head and a  
threaded shank extending from said fastener head, and wherein  
said fastener head engages an exterior surface of said chamber  
wall.

7. (original) The apparatus of claim 5 further comprising a  
gas mix plate carried by said chamber wall above said  
showerhead.

8. (original) The apparatus of claim 7 wherein each of said  
plurality of exterior fasteners comprises a fastener head and a  
threaded shank extending from said fastener head, and wherein  
said fastener head engages an exterior surface of said chamber  
wall.

9. (withdrawn) An apparatus comprising:

a process chamber having a chamber wall;

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

a showerhead provided in said process chamber;

a confine ring provided in said process chamber beneath said showerhead; and

a plurality of embedded fasteners extending through said confine ring and said showerhead and into said process chamber, with each of said plurality of embedded fasteners substantially embedded in said confine ring.

10. (withdrawn) The apparatus of claim 9 wherein each of said plurality of embedded fasteners comprises a fastener head and a threaded shank extending from said fastener head, and wherein said fastener head is substantially flush with said bottom surface of said confine ring.

11. (withdrawn) The apparatus of claim 9 wherein said process chamber comprises a gas mix plate carried by said chamber wall above said showerhead and wherein said plurality of embedded fasteners is threaded into said gas mix plate.

12. (withdrawn) The apparatus of claim 11 wherein each of said plurality of embedded fasteners comprises a fastener head and a threaded shank extending from said fastener head, and wherein said fastener head is substantially flush with said bottom surface of said confine ring.

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

13. (withdrawn) A method of mounting a showerhead in a process chamber having a chamber wall defining a chamber interior, comprising the steps of:

extending a plurality of fasteners into engagement with the showerhead and the process chamber; and

structurally isolating said plurality of fasteners from the chamber interior.

14. (withdrawn) The method of claim 13 wherein said extending a plurality of fasteners into engagement with the showerhead and the process chamber comprises the step of extending a plurality of exterior fasteners inwardly through the chamber wall and into the showerhead.

15. (withdrawn) The method of claim 13 wherein each of said plurality of fasteners comprises a fastener head and a threaded shank extending from said fastener head.

16. (withdrawn) The method of claim 15 wherein said extending a plurality of fasteners into engagement with the showerhead and the process chamber comprises the step of extending a plurality of exterior fasteners inwardly through the chamber wall and into the showerhead.

17. (withdrawn) The method of claim 13 wherein said

Applicant: Yu-Lien Huang, et al.  
Serial No.: 10/656,586  
Attorney Docket No.: 67,200-1133

extending a plurality of fasteners into engagement with the showerhead and the process chamber comprises the step of extending a plurality of embedded fasteners through the showerhead and threading said plurality of embedded fasteners into the process chamber.

18. (withdrawn) The method of claim 17 wherein each of said plurality of fasteners comprises a fastener head and a threaded shank extending from said fastener head.

19. (withdrawn) The method of claim 14 wherein said structurally isolating said plurality of fasteners from the chamber interior comprises the step of abutting the showerhead against the chamber wall.

20. (withdrawn) The method of claim 17 wherein said structurally isolating said plurality of fasteners from the chamber interior comprises the step of embedding said plurality of embedded fasteners in a confine ring disposed in the chamber interior beneath the showerhead.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- BLACK BORDERS**
- IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- FADED TEXT OR DRAWING**
- BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- SKEWED/SLANTED IMAGES**
- COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- GRAY SCALE DOCUMENTS**
- LINES OR MARKS ON ORIGINAL DOCUMENT**
- REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**